















# Peb3Le

# Powerful, easy-to-use and costeffective, the Pebble color printer personalizes and encodes all your plastic cards: identification, security, loyalty and leisure badges.

The **Pebble** prints your high resolution texts, logos, pictures, signatures and barcodes in a few seconds. It also offers optional magnetic encoding, smart card encoding and contactless card personalization.

Powerful and reliable, the Pebble is designed to answer all needs, from small card series to printing in volume.

The Pebble is a turnkey solution. Delivered as standard with user-friendly software for badge personalization and drivers for Windows™ or Mac OS X, it is as easy-to-use as a classical office printer.

The Pebble comes in three colors: Lagoon, Ruby and Glacier. Its Hi-Tech design, compactness and ergonomics allow it to integrate any reception or office desk.

With an excellent quality/price ratio, the Pebble is the referent single-sided color printer on the market.





### **Print mode**

- Color dye sublimation and monochrome thermal transfer
- Edge-to-edge printing standard

# **Printer specifications**

Integrated ribbon saver for monochrome printing

### **Print speed**

- 150 cards/hour in full color (YMCKO)
- Up to 1000 cards/hour in monochrome¹

300 dpi (11,8 dots/mm)

### Printer colors

Glacier, Lagoon or Ruby

# Software supplied

- eMedia Card Designer for designing and editing badges
- Compatible with Windows<sup>TM</sup> NT 4.0, 2000 and Xp

- For Windows™ NT 4.0, 2000 and Xp
- For Mac<sup>™</sup> OS X v10.2 and v10.3

- Printer: 2 years
- Print head: 2 years, unlimited number of prints<sup>2</sup>

- Monochrome ribbon: 1000 cards/roll (black, blue, red, green, white, gold, silver and scratch off)
- BlackWAX monochrome ribbon (for ABS and special varnished plastic cards): 1000 cards/roll
- 2 panel black monochrome ribbon (KO): 500 cards/roll
- 5 panel color ribbon (YMCKO): 200 cards/roll
- Half-panel color ribbon (YMCKO): 400 cards/roll
- Hologram ribbon: 350 cards/roll

## Card loading modes

Automatic with feeder or hand-feed

### Ontions

- HICO/LOCO magnetic stripe encoder (3-tracks), ISO 7811, field upgradeable
- Serial port (available upon study)
- Hand-feed cartridge
- 100-card additional feeder
- Suitcase for demonstration
- Cleaning kit

**Card types** 

Electrical

**Environmental** 

### Other printer models

- Pebble Mag Printer with HICO/LOCO magnetic stripe encoder ISO 7811
- Pebble Smart Printer with smart card contact station ISO 7816-2
- Pebble Contactless Printer with contactless smart card coupler
  - Under specific conditions
- 2 Clause governing the use of Evolis ribbons



names and trademarks are the property of their respective owners. October 2004. Pictures Calvez Actinic

notice. All other

All rights reserved. Evolis reserves the right to change the product specifications at any time without

2004 Evolis Card Printer.

Card format **Card thickness** Card feeder capacity Card output hopper capacity **Resident barcodes** Resident fonts Printer size **Printer weight Connections** 

PVC, Composite PVC, PET, ABS and special varnished plastic cards ISO CR-80 - ISO 7810 (53,98 mm x 85,60 mm - 3.375" x 2.125") From 0,25 mm (10 mil) to 1 mm (40 mil)

300 cards (0.25 mm - 10 mil) - 100 cards (0.76 mm - 30 mil) 150 cards (0,25 mm - 10 mil) - 50 cards (0,76 mm - 30 mil)

Code 39, Code 2/5 interleaved Arial normal 100, Arial bold 100

Height: 192 mm (7.55") - Length: 396 mm (15.59") - Width: 235 mm (9.25") 5,9 Kg (13 lbs)

USB and Centronics parallel ports (cables supplied) 110~230 Volts CA, 60~50 Hertz

- Min / max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing Min / max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air



Headquarters: **Evolis Card Printer** 

29, avenue de la Fontaine · Z.I. Angers-Beaucouzé · 49070 BEAUCOUZE · France Tel: +33 (0) 241 367 606 · Fax: +33 (0) 241 367 612 · info@evolis.com